

Survey of Section 20 T. 1 R. 1 N.



FIELD NOTES.

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
A) perpendicular							
legumose	10	S 76° E	77				
B) stone		S 87° W	16				
stone		S 4° W	14				
C) Burdock	10	S 4° W	47½				
legumose	2	S 57° W	34				
D) Burdock	2	S 61° E	20				
iron pin		S 23½° W	34½				
E) felsin	4	S 4½° E	42				
hackberry	2	S 9½° E	18¾				
wehew	2	S 1½° E	5				

- May 13 1907 The first time the publication of the Blount County Telephone was not pursuant thereto and organized by qualifying Henry W. Antland Richard R. L. of Chambers William A. Lane and others then returned to meet May 25 1907 at 7 a.m.
- May 25 1907 May 25th met according to adjournment of May 13 and qualified Andrew H. Hedley Chapman instead of William A. Lane we then proceeded to make the following survey as per plat and notes in section 35 T 7 R 1 W perpetuated the center of said section by marking new witness corners 10 m S 70° E 77 lks established the distance between the center and NW 1/4 m p witness by stone S 87° W 16 lks stone S 40° W 14 lks established a line 99 rods 12 1/2 ft E. of the center of the NW quarter of said section witness by Black Walnut 10 m S 46° W 47 1/2 lks cypress 2 m S 57° W 34 lks Thorne at 17 1/2 W 16 rods 10 lks to a stone witness by black Walnut 2 m S 61° E 20 lks From pin in stone S 23 1/2° W 34 1/2 lks established a stone 16 rods 10 lks E. of the center of the NW quarter witness by elm 4 m S 42° E 42 lks hackberry 2 m S 94° E 17 1/2 lks Weherry 2 m S 11 1/2° E 50 lks